

Commissioner for Patents
Page 2

Serial No.: 09/662,337

AMENDMENTS TO THE CLAIMS

This listing of the claims replaces all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1. (Currently Amended) A method of validating a connection mapped through a communications network between first and second end-nodes, the method comprising the steps of:
 - a) at the first end-node, inserting performance monitor (PM) information into a predetermined location ~~within a payload portion of a payload envelope;~~
 - b) transporting the payload envelope through the connection to the second end-node; and
 - c) at the second end-node, extracting the PM information from the predetermined location within the payload envelope.

wherein the payload envelope is an augmented synchronous payload envelope (SPE) having a payload capacity that is expanded relative to a standard SONET/SDH frame by an amount sufficient to accommodate the PM information.

2. (Cancelled)
3. (Cancelled)
4. (Cancelled)

Commissioner for Patents
Page 3

Serial No.: 09/662,337

5. (Currently Amended) A method as claimed in claim ~~21~~, further comprising a step of enabling the first and second nodes to pointer process the augmented SPE.
6. (Original) A method as claimed in claim 5, further comprising a step of providing an extended range of valid payload pointer values that can be pointer processed within a node participating in the connection.
7. (Original) A method as claimed in claim 1, wherein each node in the network is adapted to support a plurality of connection layers and the connection is mapped on one of the plurality of connection layers.
8. (Original) A method as claimed in claim 7, wherein PM information respecting each layer is inserted into a respective predetermined location of the payload envelope.
9. (Original) A method as claimed in claim 1, wherein the step of inserting PM information comprises a step of inserting one or more of a Trace field; a Parity field; and an indicator field.
10. (Original) A method as claimed in claim 9, wherein the step of inserting a Trace field comprises inserting a nibble of a trace message for communicating information concerning the connection.
11. (Original) A method as claimed in claim 10,

Commissioner for Patents
Page 4

Serial No.: 09/662,337

wherein the step of inserting the nibble of a trace message comprises a step of inserting successive nibbles of the trace message into respective successive signals until an entire trace message has been sent.

12. (Original) A method as claimed in claim 10, wherein the step of inserting a Trace field comprises repeating the trace message after the entire trace message has been sent.
13. (Original) A method as claimed in claim 9, wherein the step of inserting a parity field comprises a step of calculating a parity value in respect of a data signal, and inserting the parity value into a next augmented SPE to be transmitted.
14. (Original) A method as claimed in claim 13, wherein the parity value is a BIP-8.
15. (Original) A method as claimed in claim 14, wherein the parity value is calculated starting after an H2 byte of a transport overhead (TOH) portion of the signal, and incorporates all payload envelope bytes until the H2 byte of a next data signal.
16. (Original) A method as claimed in claim 9, wherein the step of inserting an indicator field comprises a step of accumulating an error count in respect of the data signal.

Commissioner for Patents
Page 5

Serial No.: 09/662,337

17. (Original) A method as claimed in claim 16, wherein the error count is a BIP-8.
18. (Original) A method as claimed in claim 1, wherein the step of extracting the PM information comprises a step of extracting one or more of a trace field; a parity field; and an indicator field.
19. (Original) A method as claimed in claim 18, further comprising a step of converting the payload envelope into a SONET/SDH SPE having a conventional size and format.
20. (Original) A method as claimed in claim 18, wherein the step of extracting a parity field further comprises a step of calculating a parity value in respect of the received data signal.
21. (Original) A method as claimed in claim 20, further comprising a step of comparing the recalculated parity value with a received parity value contained in the extracted parity field to obtain an error count.
22. (Original) A method as claimed in claim 21, further comprising a step of accumulating the error count value in respect of the received data signal.
23. (Original) A method as claimed in claim 18, wherein the step of extracting an indicator field further comprises the steps of:

Commissioner for Patents
Page 6

Serial No.: 09/662,337

- a) monitoring the indicator field of each successive received data signal; and
 - b) asserting an AIS state if the indicator field of each of a first predetermined number of successive data signals contains a first predetermined value.
24. (Original) A method as claimed in claim 23, further comprising a step of de-asserting the AIS state if the indicator field of each of the first predetermined number of successive data signals contains a value other than the first predetermined value.
25. (Original) A method as claimed in claim 23, wherein the first predetermined number of successive data signals is three.
26. (Original) A method as claimed in claim 23, wherein the first predetermined value is binary "1111".
27. (Currently Amended) A method as claimed in claim ~~1823~~, wherein the step of extracting an indicator field further comprises the steps of:
- a) monitoring the indicator field of each successive received signal; and
 - b) asserting an RDI state if the indicator field of each of a second predetermined number of successive signals contains a second predetermined value.

Commissioner for Patents
Page 7

Serial No.: 09/662,337

28. (Original) A method as claimed in claim 27, wherein the predetermined number of successive data signals is three.
29. (Original) A method as claimed in claim 27, wherein the second predetermined value is binary "1100".
30. (Currently Amended) A system of validating a connection mapped through a communications network between first and second end-nodes, the system comprising:
- a) means for inserting performance monitor (PM) information into a predetermined location within a payload envelope ~~a payload portion of~~ at the first end-node;
 - b) means for transmitting the payload envelope through the connection to the second end-node; and
 - c) means for extracting the PM information from the payload envelope at the second end-node.
- wherein the payload envelope is an augmented synchronous payload envelope (SPE) having a payload capacity that is expanded relative to a standard SONET/SDH frame by an amount sufficient to accommodate the PM information.
31. (Cancelled)
32. (Currently Amended) A system as claimed in claim ~~31~~30, wherein each of the first and second

Commissioner for Patents
Page 8

Serial No.: 09/662,337

nodes comprise a respective pointer processor state machine adapted to control pointer processing of the augmented SPE.

33. (Currently Amended) A system as claimed in claim 32, wherein each pointer processor state machine is adapted to accommodate an extended a range of valid payload pointer values, relative to a—that of the SONET/SDH SPE standard.
34. (Original) A system as claimed in claim 30, wherein each node in the network is adapted to support a plurality of connection layers and the connection is mapped on one of the plurality of connection layers.
35. (Original) A system as claimed in claim 34, wherein PM information respecting each layer is inserted into a respective predetermined location of the payload envelope.
36. (Original) A system as claimed in claim 30, wherein the PM information comprises any one or more of a Trace field; a Parity field; and an Indicator field.
37. (Original) A system as claimed in claim 36, wherein the Trace field contains a nibble of a trace message for communicating information concerning the connection.
38. (Original) A system as claimed in claim 37, wherein successive nibbles of the trace message

Commissioner for Patents
Page 9

Serial No.: 09/662,337

are inserted into respective successive synchronous containers until an entire trace message has been sent.

39. (Original) A system as claimed in claim 37, wherein the trace message is repeated after the entire trace message has been sent.
40. (Currently Amended) A system as claimed in claim 36, further comprising:
- a) means for calculating a parity value in respect of a data signal; and
 - b) means for inserting the parity value into the parity field of a next synchronous container to be transmitted.
41. (Original) A system as claimed in claim 40, wherein the parity value is a BIP-8.
42. (Original) A system as claimed in claim 41, wherein the parity value is calculated starting after an H2 byte of a transport overhead (TOH) portion of the signal, and incorporates all payload envelope bytes until the H2 byte of a next data signal.
43. (Original) A system as claimed in claim 36, wherein the indicator field contains an error count accumulated in respect of the data signal.
44. (Original) A system as claimed in claim 43, wherein the error count is a BIP-8.
45. (Original) A system as claimed in claim 30, wherein the means for extracting the PM

Commissioner for Patents
Page 10

Serial No.: 09/662,337

information comprises means for extracting one or more of a trace field; a parity field; and an indicator field.

46. (Original) A system as claimed in claim 45, wherein the means for extracting a parity field further comprises means for calculating a parity value in respect of the received data signal.
47. (Original) A system as claimed in claim 46, further comprising means for comparing the recalculated parity value with a received parity value contained in the extracted parity field to obtain an error count.
48. (Original) A system as claimed in claim 47, further comprising means for accumulating the error count value in respect of the received payload envelope.
49. (Original) A system as claimed in claim 45, wherein the means for extracting an indicator field further comprises:
- a) means for monitoring the indicator field of each successive received payload envelope; and
 - b) means for asserting an AIS state if the indicator field of each of a first predetermined number of successive payload envelope containers contains a first predetermined value.
50. (Currently Amended) A system as claimed in claim 49, further comprising means for de-

Commissioner for Patents
Page 11

Serial No.: 09/662,337

asserting the AIS state if the Indicator field of each of the first predetermined number of successive payload envelopes contains a value other than the first predetermined value.

51. (Currently Amended) A system as claimed in claim 49, wherein the first predetermined number of successive payload envelopes is three.
52. (Original) A system as claimed in claim 49, wherein the first predetermined value is binary "1111".
53. (Original) A system as claimed in claim 45, wherein the means for extracting an indicator field further comprises:
 - a) means for monitoring the indicator field of each successive received payload envelope; and
 - b) means for asserting an RDI state if the indicator field of each of a second predetermined number of successive signals contains a second predetermined value.
54. (Original) A system as claimed in claim 53, wherein the predetermined number of successive payload envelopes is three.
55. (Original) A system as claimed in claim 53, wherein the second predetermined value is binary "1100".
56. (Currently Amended) An apparatus for validating a connection mapped through a communications network

Commissioner for Patents
Page 12

Serial No.: 09/662,337

between first and second end-nodes, the apparatus comprising:

- a) means for inserting performance monitor (PM) information into a predetermined location ~~within a payload portion of a payload envelope~~; and
- b) means for transmitting the payload envelope through the connection.

wherein the payload envelope is an augmented synchronous payload envelope (SPE) having a payload capacity that is expanded relative to a standard SONET/SDH frame by an amount sufficient to accommodate the PM information.

57. (Cancelled)

58. (Currently Amended) An apparatus as claimed in claim ~~57~~56, wherein each of the first and second nodes comprise a respective pointer processor state machine adapted to control pointer processing of the augmented SPE.

59. (Currently Amended) An apparatus as claimed in claim 58, wherein each pointer processor state machine is adapted to accommodate an extended range of valid payload pointer values, relative to ~~a~~-that of the SONET/SDH SPE standard.

60. (Original) An apparatus as claimed in claim 56, wherein each node in the network is adapted to support a plurality of connection layers and the connection is mapped on one of the plurality of connection layers.

Commissioner for Patents
Page 13

Serial No.: 09/662,337

61. (Original) An apparatus as claimed in claim 60, wherein PM information respecting each layer is inserted into a respective predetermined location of the payload envelope.
62. (Original) An apparatus as claimed in claim 56, wherein the PM information comprises any one or more of a Trace field; a Parity field; and an Indicator field.
63. (Original) An apparatus as claimed in claim 62, wherein the Trace field contains a nibble of a trace message for communicating information concerning the connection.
64. (Currently Amended) An apparatus as claimed in claim 63, wherein successive nibbles of the trace message are inserted into respective successive payload envelopes until an entire trace message has been sent.
65. (Original) An apparatus as claimed in claim 63, wherein the trace message is repeated after the entire trace message has been sent.
66. (Currently Amended) An apparatus as claimed in claim 65, further comprising:
 - a) means for calculating a parity value in respect of a data signal; and
 - b) means for inserting the parity value into the Parity field of a next payload envelope to be transmitted.
67. (Original) An apparatus as claimed in claim 66, wherein the parity value is a BIP-8.

Commissioner for Patents
Page 14

Serial No.: 09/662,337

68. (Original) An apparatus as claimed in claim 66, wherein the parity value is calculated starting after an H2 byte of a transport overhead (TOH) portion of the signal, and incorporates all payload envelope bytes until the H2 byte of a next data signal.
69. (Original) An apparatus as claimed in claim 62, wherein the indicator field contains an error count accumulated in respect of the data signal.
70. (Original) An apparatus as claimed in claim 69, wherein the error count is a BIP-8.
71. (Currently Amended) An apparatus for validating a connection mapped through a communications network between first and second end-nodes, the apparatus comprising:
- a) means for receiving a payload envelope through the connection; and
 - b) means for extracting performance monitor (PM) information from a predetermined location within a payload portion of a an augmented synchronous payload envelope having a payload capacity that is expanded relative to a standard SONET/SDH frame by an amount sufficient to accommodate the PM information.
72. (Original) An apparatus as claimed in claim 71, wherein the means for extracting PM information comprises means for extracting one or more of a trace field; a parity field; and an indicator field.

Commissioner for Patents
Page 15

Serial No.: 09/662,337

73. (Original) An apparatus as claimed in claim 72, wherein the means for extracting a Parity field further comprises means for calculating a parity value in respect of the received payload envelope.
74. (Original) An apparatus as claimed in claim 73, further comprising means for comparing the recalculated parity value with a received parity value contained in the extracted Parity field to obtain an error count.
75. (Original) An apparatus as claimed in claim 74, further comprising means for accumulating the error count value in respect of the received payload envelope.
76. (Original) An apparatus as claimed in claim 72, wherein the means for extracting an indicator field further comprises:
- a) means for monitoring the Indicator field of each successive received synchronous container; and
 - b) means for asserting an AIS state if the Indicator field of each of a first predetermined number of successive payload envelope containers contains a first predetermined value.
77. (Previously Presented) An apparatus as claimed in claim 76, further comprising means for de-asserting the AIS state if the indicator field of each of the first predetermined number of successive payload envelopes contains a value

Commissioner for Patents
Page 16

Serial No.: 09/662,337

other than the first predetermined value.

78. (Previously Presented) An apparatus as claimed in claim 76, wherein the first predetermined number of successive payload envelopes is three.
79. (Original) An apparatus as claimed in claim 76, wherein the first predetermined value is binary "1111".
80. (Original) An apparatus as claimed in claim 72, wherein the means for extracting an indicator field further comprises:
- a) means for monitoring the indicator field of each successive received payload envelope; and
 - b) means for asserting an RDI state if the indicator field of each of a second predetermined number of successive signals contains a second predetermined value.
81. (Previously Presented) An apparatus as claimed in claim 80, wherein the predetermined number of successive payload envelopes is three.
82. (Original) An apparatus as claimed in claim 80, wherein the second predetermined value is binary "1100".
83. (New) The method as claimed in claim 1 wherein the augmented synchronous payload envelope has at least one additional column of payload for accommodating the PM information.

Commissioner for Patents
Page 17

Serial No.: 09/662,337

84. (New) The system as claimed in claim 30 wherein the augmented synchronous payload envelope has at least one additional column of payload for accommodating the PM information.
85. (New) The apparatus as claimed in claim 56 wherein the augmented synchronous payload envelope has at least one additional column of payload for accommodating the PM information.
86. (New) The apparatus as claimed in claim 71 wherein the augmented synchronous payload envelope has at least one additional column of payload for accommodating the PM information.